

Wireless Weight Indicator



Special Features :

- Adopts Σ - Δ A/D conversion technology.
- Keyboard calibration, easy to operate.
- Able to setup zero(auto/manual) range.
- Weighing data save protection in case of power off.
- Battery charger with several protection modes to extend life of rechargeable battery.
- Standard RS232 communication interface(optional).
- Portable design, packed in portable box, easy to operate outdoor.
- Adopt SMT technology, reliable and high quality.
- LCD display with dot character with backlight, readable in aphotic areas.
- Gathering up to data records of 2000 weighing, records can be sorted, searched and printed.
- Standard parallel print interface(EPSON printer)
- With rechargeable 7.2V/2.8AH battery for indicator, no memory. Scale body with power supply of DC 6V/4AH battery.
- Power saving mode, indicator will turn off automatically after 30minutes with no operation.

Technical Data:

A/D Conversion Method:	Σ - Δ
Input Signal Range:	- 3mV~15mV
Load Cell Excitation:	DC 5V
Max. Connection Number Of Load Cell:	4 at 350 ohm
Load Cell Connection Mode:	4 wire
Verified Counts:	3000
Max. External Counts:	15000
Division:	1/2/5/10/20/50 optional
Display:	LCD display with backlight
Clock:	real clock without effect on power off
Wireless Transmission Frequency:	450MHz
Wireless Transmission Distance:	800 meters (in wide place)
Option:	RS232 communication interface

- Built-in printer;
- Clock for time/date printing;
- Rechargeable battery and charger;
- LCD display with backlight;